

PRODUCT CLASSIFICATION ACCORDING TO THEIR RESISTANCE AGAINST HUMIDITY IN INTERIOR SURROUNDINGS FOLLOWING EN 13120 www.tenditalia.com

L1: Site with poor hygrometry (W/n)<2,5g/m3





Office blocks with no air conditioning, day schools, housing with controlled mechanical ventilation systems, and specialized systems which remove water vapor at the point of origination as soon as they are produced (hoods, etc.); industrial buildings used as warehouses, workshops, etc. where no vapor is produced; sports locations not open to the public (except for swimming pools and skating rinks).

L2: Site with average hygrometry 2,5<= (W/n)<2,5g/m3



Living quarters, including kitchens and bathrooms, which are properly heated and ventilated without overcrowding; public facilities and outbuildings; cultural and multi-functional buildings


FABRIC	Roller 	Pleated 	Verticals 
ASPEN	X	-	-
BAMBU'	-	X	-
BLOOM	-	X	-
BOBIL	-	X	-
CAMPER	-	X	-
CAMPER WHITE	-	X	-
COMFORT	X	X	-
E'LITE	X	X	-
EUROBLACKOUT	X	X	-
EURO BLACKOUT TREND	X	X	-
EXTRA ASPEN	X	-	X
GARDEN	-	X	-
GEA	X	X	-
GREENEBO FR	X	X	-
KOOB FR	X	-	X
LOTO	X	-	-
RING	-	X	-
SKY	-	X	-
SILENCE	-	X	-

*W/n: indoor humidity is the ratio between the amount of steam produced in a room in 1 hour (gr/h) and the air exchange in the room (m3/h); the unit of measurement is g/m3.




PRODUCT CLASSIFICATION ACCORDING TO THEIR RESISTANCE AGAINST HUMIDITY IN INTERIOR SURROUNDINGS FOLLOWING EN 13120 www.tenditalia.com

L3: Site with high hygrometry

$$5 \leq (W/n) < 2,5 \text{ g/m}^3$$



Domestic properties with poor ventilation or over-occupancy; areas with a high level of occupancy, either human or animal, such as rearing sheds, stables, certain workshops, etc.; industrial units with controlled humidity due to certain manufacturing processes; air conditioned




FABRIC	Roller 	Pleated 	Verticals 
BUSINESS	X	-	X
EXTRA BUSINESS	X	-	X
FLASH	-	-	X
GREEN OFFICE	X	-	X
LIFE	X	X	-
MIAMI	X	-	X
NATURA FR	X	-	X
PANDA	X	-	-
PATAGONIA + PAT FR	X	-	X
RESPECT	X	-	-
SHANTUNG	X	-	X
VANITY UP	X	X	-
VANITY UP FR	X	X	-
VENTO FR	X	-	X

PRODUCT CLASSIFICATION ACCORDING TO THEIR RESISTANCE AGAINST HUMIDITY IN INTERIOR SURROUNDINGS FOLLOWING EN 13120 www.tenditalia.com

L4: Site with very high hygrometry (W/n)>7,5g/m³



Specialized industrial areas requiring a relatively high level of humidity, communal washrooms which are constantly in use; places with a very high level of water vapor production such as swimming pools, canning factories, dry cleaners, industrial dairies, bottle washing plants, breweries, polishing workshops, communal kitchens, industrial laundries, spinning weaving and tanning workshops, etc.

FABRIC	Roller 	Pleated 	Verticals 
CLOSE	X	-	-
NET	X	-	X
TEXFIVE	X	-	-
TEXNET	X	-	X
TEXONE	X	-	-

L5: inospitable surroundings (W/n)>7,5g/m³



Site where the atmosphere is aggressive, (chemically corrosive, corrosive sprays, etc...), even if it is only intermittent.

*W/n: indoor humidity is the ratio between the amount of steam produced in a room in 1 hour (gr/h) and the air exchange in the room (m³/h); the unit of measurement is g/m³.